

Product Name:SLT1A

Product Model: SLT-10

Product Description: 采用一体化设计，安装简便，各组件均可方便更换，节省成本。智能控制器匹配 P I R 运动红外线感应器，保证灯具的有效照明能力。专业防水设计，防护等级 I P66。采用专用对插接头，颜色防呆设计，具有防接错等功能。支持多种灯臂，适用不同纬度地域及不同形式灯杆安装要求。

With integrated design, easy installation, the components can be easily replaced, cost savings. The intelligent controller matches the P I R motion infrared sensor to ensure the effective lighting capability of the fixture. Professional waterproof design, protection class I P66. Using a dedicated plug connector, color foolproof design, with anti-fault and other functions. Support a variety of lamp arm, for different latitude and different forms of poles installation requirements.

Technical Parameters:

产品型号 Model	SLT-10	放电时间 Operating time	满足每天 7~8 小时有效光照充电,可达到全功率≥12 小时 / 智能模式 4~5 天 Full power≥12 hours, Intelligent mode 4-5 days
产品功率 Power	10W	太阳能板转化率 Solar panel conversion rate	≥17%
太阳能电池板 Solar pane	17.5W 单晶硅 17.5W monocrystalline silicon	灯珠色温 CCT	4500K~5000K(可 根据客户需要定制 4500K~5000K
电池 Battery	9.6AH 磷酸铁锂 9.6AH Lithium-ion Li Fepo4 batteries	安装高度 Installation height	4~6m
整灯光效 Lighting efficacy	≥160LM/W	灯杆直径 Pole diameter	50~60mm
发光角度 Beam angle	150° x70°	工作温度 Operating temperature	-10° C ~ 60° C
防护等级 Waterproof rate	I P66	质保时间 Warranty	3 年